# **IMG Chemicals Corporation**

Material Safety Data Sheet

# 1. PRODUCT AND COMPANY IDENTIFICATION:

Company Contact Information IMG Chemicals Corporation

P.O. Box 52461 Atlanta, GA 30355 USA

Telephone: +1(678) 513-69-23 Emergency Telephone Number CHEMTREC: 800-424-9300 (24 hours) Product Name: Complete Fuel System Cleaner

Item №: **MG-308** Product Type: Mixture

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

(N/E = Not Established; N/E: = Not Established)

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
68476346	Petroleum distillate, Aliphatic	70-100							100 ppm	
Proprietary	Polyether amine	1-10						N/E	N/E	

# 3. HAZARDS IDENTIFICATION

**Hazard Category:** Acute, Fire

Hazardous Identification Information: Danger: Harmful or fatal if swallowed. Eye and skin irritant. Combustible.

# 4. FIRST AID MEASURES

**Route(s) of Entry:** Absorption, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):** 

**Signs and Symptoms:** 

**Eye Contace:** Irritant. Prolonged contact may cause conjunctivitis. **Skin Contact:** Irritant. Defatting of tissue, dermatitis may occur.

**Inhalation:** Irritant to mucous membranes. Repeated exposure may cause narcosis.

**Ingestion:** HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat & stomach.

## **Medical Conditions Generally Aggravated by Exposure:**

## **Emergency and First Aid Procedures:**

**Eye Contact:** Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical at-

tention.

**Skin Contact:** Wash with soap and water thoroughly. If adverse effects persist, get prompt medical

attention. Launder contaminated clothing before reuse.

**Inhalation:** Remove to fresh air. If breathing becomes difficult get prompt medical attention.

**Ingestion:** DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergen-

cy room immediately.

**Other Health Warnings:** Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia

and pulmonary edema which is a potentially fatal condition.

## **5. FIRE FIGHTING MEASURES**

Upper Explosive Limit:N/DLower Explosive Limit:N/DFlash Point:140F

**Fire Extinguishing Media:** Water Fog, Foam, Carbon Dioxide, Dry Chemical

**F.P. Method:** TCC

**Special Fire Fighting Procedures:** Wear self-contained positive pressure breathing apparatus and protective clothes. Cool

containers with a water fog. Do not use forced water stream as this could cause the fire to

spread.

**Unusual Fire and Explosion:** Toxic fumes, gases or vapors may evolve on burning. Vapors may be havier that air and may

travel along the ground to a distant ignition source and flash back

<u>Product Name:</u> Complete Fuel System Cleanert

Item №: MG-308

## 6. ACCIDENTAL RELEASE MEASURES

# Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occured.

#### 7. HANDLING AND STORAGE

**Precautions to be Taken:** Handling: Use with adequate ventilation and proper protective equipment.

Other Precautions: Keep container closed tightly when not in use. Combustible. Store in a cool place below 120

F away from acids, ignition sources and oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Ventilation Requirements:** See Section 2 for applicable exposure limits. Maintain adequate ventilation. Avoid breath-

ing vapors. In restricted areas, use approved chemical filters designed to remove vapor. In confined areas, use approved air line type respirator or hood. A self-contained breathing

apparatus is required for vapor concentrations above TLV limit

**Personal Protective Equipment:** See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety

glasses, gloves, and apron.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: >300 F
Melting Point: N/A
Evaporation Rate (Butyl Acetate = 1): N/D
Vapor Pressure (mm Hg.): N/D
Specific Gravity (H20 = 1): 0.86000
Vapor Density (AIR = 1): N/D
Solubility In Water: Insoluble

**Appearance and Odor:** Light yellow--amber liquid with petroleum odor.

# 10. STABILITY AND REACTIVITY

**Stability:** Stability:

Incompatibility (Materials to Avoid): Oxidizing agents. Open flame, or spark, and acids

**Decomposition/By Products:** Fire: Normal products of combustion: carbon monoxide, carbon dioxide, and acrid smoke.

Nitrogen and sulfur oxides.

**Hazardous Polymerization:** Will not occur

# 11. TOXICOLOGICAL INFORMATION

N/D

# 12. ECOLOGICAL INFORMATION

N/C

# 13. DISPOSAL CONSIDERATIONS

**DISPOSAL:** This container may be recycled in a recycling centers when empty. Before offering for recy-

cling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accor-

dance with all local, state government and federal laws and regulations

<u>Product Name:</u> Complete Fuel System Cleanert

<u>Item №:</u> MG-308

## 14. TRANSPORT INFORMATION

UN1993, FLAMMABLE LIQUID, N.O.S., (Fuel Oil, No. 2) CLASS 3, PG III, LTD QTY, FP 85C (CC), MARINE POLLUTANT EMS: F-E,S-E

BOXES OF 12 EACH 11.8 OZ PLASTIC BOTTLE PLASTIC CAP

#### 15. REGULATORY INFORMATION

See Section 2 for SARA Reportable Chemicals.

**USA TSCA:** All components of this material are listed on the US TSCA Inventory. This fuel additive is

registered in the United States

**Warning:** This product contains a chemical known to the State of California to cause cancer or birth defects or other reproductive harm..

# **16. OTHER INFORMATION**

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 2, REACTIVITY 0 **Estimated HMIS Classification:** FLAMMABILITY 2, REACTIVITY 0, HEALTH 2

N/E: Not EstablishedN/D: Not DeterminedN/A: Not ApplicableN/AV: Not Available

Revision Date: 09/10/2013