

# IMG Chemicals Corporation

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION:

Company Contact Information  
IMG Chemicals Corporation  
P.O. Box 52461 Atlanta, GA 30355 USA  
Telephone: +1(678) 513-69-23  
Emergency Telephone Number  
CHEMTREC: 800-424-9300 (24 hours)

Product Name: **Diesel Fuel De-Gel**  
Item N<sup>o</sup>: **MG-336**  
Product Type: Mixture

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

(N/E = Not Established; N/E: = Not Established)

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
111762	Ethylene Glycol butyl Ether	25.0-40.0 %								
68476302	Fuel Oil, no.2	60.0-75.0 %								

### 3. HAZARDS IDENTIFICATION

**Hazard Category:** Acute, Fire

**Hazardous Identification Information:** Combustible. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Combustible

### 4. FIRST AID MEASURES

**Route(s) of Entry:** Absorption, Eye, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

**Signs and Symptoms:**

**Eye Contact:** Irritant. Prolonged contact may cause conjunctivitis.  
**Skin Contact:** Irritant. Defatting of tissue, dermatitis may occur.  
**Inhalation:** Irritant to mucous membranes. Repeated exposure may cause narcosis.  
**Ingestion:** HARMFUL OR FATAL IF SWALLOWED.

**Medical Conditions Generally Aggravated by Exposure:** None Known

**Emergency and First Aid Procedures:**

**Eye Contact:** Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.  
**Skin Contact:** Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse  
**Inhalation:** Remove to fresh air. If breathing becomes difficult get prompt medical attention.  
**Ingestion:** DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

**Other Health Warnings:** Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

**Product Name:** Diesel Fuel De-Gel  
**Item №:** MG-336

## 5. FIRE FIGHTING MEASURES

**Upper Explosive Limit:** N/D  
**Lower Explosive Limit:** N/D  
**Flash Point:** 105°F  
**Fire Extinguishing Media:** Water Fog, Foam, Carbon Dioxide, Dry Chemical  
**F.P. Method:** TCC

**Special Fire Fighting Procedures:** Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread.

**Unusual Fire and Explosion:** Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back.

## 6. ACCIDENTAL RELEASE MEASURES

### Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

## 7. HANDLING AND STORAGE

**Precautions to be Taken:** Handling: Use with adequate ventilation and proper protective equipment. Do not use near fire, sparks, or flame. Store in cool, well ventilated area below 120°F away from heat sources. Avoid contact with alkalis and strong oxidizing agents. Keep containers tightly closed

**Other Precautions:** Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.  
KEEP AWAY FROM CHILDREN AND ANIMALS!

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Ventilation Requirements:** See Section 2 for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

**Personal Protective Equipment:** See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, apron and approved respirator

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** 315°F  
**Melting Point:** N/A  
**Evaporation Rate (Butyl Acetate = 1):** N/D  
**Vapor Pressure (mm Hg.):** N/D  
**Specific Gravity (H<sub>2</sub>O = 1):** 0.88700  
**Vapor Density (AIR = 1):** N/D  
**Solubility In Water:** Insoluble  
**Appearance and Odor:** Light Straw color, characteristic aromatic odor

## 10. STABILITY AND REACTIVITY

**Stability:** Stable

**Incompatibility (Materials to Avoid):** Oxidizing agents.

**Decomposition/By Products:** Normal products of combustion: carbon monoxide, carbon dioxide, smoke and Nitrogen, Sulfur Oxides

**Hazardous Polymerization:** Will not occur

## 11. TOXICOLOGICAL INFORMATION

N/E

**Product Name:**  
**Item №:**

**Diesel Fuel De-Gel**  
**MG-336**

## 12. ECOLOGICAL INFORMATION

N/E

## 13. DISPOSAL CONSIDERATIONS

### DISPOSAL:

This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

## 14. TRANSPORT INFORMATION

UN1223, FLAMMABLE LIQUIDS, N.O.S., (Kerosene, Ethylene glycol butyl ether)

CLASS 3, PG III, LTD QTY, FP 66.7C (CC), MARINE POLLUTANT

EMS F-E,S-E

BOXES OF 12 EACH 11.8 OZ PLASTIC BOTTLE, PLASTIC CAP

## 15. REGULATORY INFORMATION

See Section 2 for SARA Reportable Chemicals.

### USA TSCA:

All components of this material are listed on the US TSCA Inventory.

This fuel additive is registered in the United States

**Warning:** This product contains chemicals known to the State of California to cause cancer or birth defects or other reproductive harm.

## 16. OTHER INFORMATION

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.  
KEEP AWAY FROM CHILDREN AND ANIMALS!

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 2, REACTIVITY 0

**Estimated HMIS Classification:** FLAMMABILITY 2, REACTIVITY 0, HEALTH 2

**N/E:** Not Established  
**N/D:** Not Determined  
**N/A:** Not Applicable  
**N/AV:** Not Available

Revision Date: 09/10/2013