

IMG Chemicals Corporation

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION:

Company Contact Information
IMG Chemicals Corporation
P.O. Box 52461 Atlanta, GA 30355 USA
Telephone: +1(678) 513-69-23
Emergency Telephone Number
CHEMTREC: 800-424-9300 (24 hours)

Product Name: **Diesel Fuel De-Gel**
Item N^o: **MG-337**
Product Type: Mixture

2. COMPOSITION/INFORMATION ON INGREDIENTS

(N/E = Not Established; N/E: = Not Established)

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
111762	Ethylene Glycol butyl Ether	25.0-40.0 %								
68476302	Fuel Oil, no.2	60.0-75.0 %								

3. HAZARDS IDENTIFICATION

Hazard Category: Acute, Fire

Hazardous Identification Information: Combustible. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Combustible

4. FIRST AID MEASURES

Route(s) of Entry: Absorption, Eye, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.
Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.
Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis.
Ingestion: HARMFUL OR FATAL IF SWALLOWED.

Medical Conditions Generally Aggravated by Exposure: None Known

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.
Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse
Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.
Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Other Health Warnings: Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Product Name: Diesel Fuel De-Gel
Item №: MG-337

5. FIRE FIGHTING MEASURES

Upper Explosive Limit: N/D
Lower Explosive Limit: N/D
Flash Point: 105°F
Fire Extinguishing Media: Water Fog, Foam, Carbon Dioxide, Dry Chemical
F.P. Method: TCC

Special Fire Fighting Procedures: Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread.

Unusual Fire and Explosion: Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back.

6. ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

7. HANDLING AND STORAGE

Precautions to be Taken: Handling: Use with adequate ventilation and proper protective equipment. Do not use near fire, sparks, or flame. Store in cool, well ventilated area below 120°F away from heat sources. Avoid contact with alkalis and strong oxidizing agents. Keep containers tightly closed

Other Precautions: Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.
KEEP AWAY FROM CHILDREN AND ANIMALS!

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: See Section 2 for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment: See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, apron and approved respirator

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 315°F
Melting Point: N/A
Evaporation Rate (Butyl Acetate = 1): N/D
Vapor Pressure (mm Hg.): N/D
Specific Gravity (H₂O = 1): 0.88700
Vapor Density (AIR = 1): N/D
Solubility In Water: Insoluble
Appearance and Odor: Light Straw color, characteristic aromatic odor

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility (Materials to Avoid): Oxidizing agents.

Decomposition/By Products: Normal products of combustion: carbon monoxide, carbon dioxide, smoke and Nitrogen, Sulfur Oxides

Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

N/E

Product Name:
Item №:

Diesel Fuel De-Gel
MG-337

12. ECOLOGICAL INFORMATION

N/E

13. DISPOSAL CONSIDERATIONS

DISPOSAL:

This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

14. TRANSPORT INFORMATION

UN1223, FLAMMABLE LIQUIDS, N.O.S., (Kerosene, Ethylene glycol butyl ether)
CLASS 3, PG III, LTD QTY, FP 66.7C (CC), MARINE POLLUTANT
EMS F-E,S-E
BOXES OF 12 EACH 33.8 OZ PLASTIC BOTTLE, PLASTIC CAP

15. REGULATORY INFORMATION

See Section 2 for SARA Reportable Chemicals.

USA TSCA:

All components of this material are listed on the US TSCA Inventory.

This fuel additive is registered in the United States

Warning: This product contains chemicals known to the State of California to cause cancer or birth defects or other reproductive harm.

16. OTHER INFORMATION

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.
KEEP AWAY FROM CHILDREN AND ANIMALS!

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 2, REACTIVITY 0

Estimated HMIS Classification: FLAMMABILITY 2, REACTIVITY 0, HEALTH 2

N/E: Not Established
N/D: Not Determined
N/A: Not Applicable
N/AV: Not Available

Revision Date: 09/10/2013