

# IMG Chemicals Corporation

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION:

Company Contact Information  
IMG Chemicals Corporation  
P.O. Box 52461 Atlanta, GA 30355 USA  
Telephone: +1(678) 513-69-23  
Emergency Telephone Number  
CHEMTREC: 800-424-9300 (24 hours)

Product Name: **Silicone Lubricant**  
Item №: **MG-501**  
Product Type: Mixture

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

(N/E = Not Established; N/E: = Not Established)

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
111762	2-Butoxyethanol	1-2					X	25 ppm	25 ppm	
8052413	Aliphatic Hydrocarbon Solvent	40.0 - 70.0						100 ppm	100 ppm	
124389	Carbon dioxide	3.0 - 4.0						N/AV	5000 ppm	
63148629	Dimethyl Polysiloxane	6-7						N/E	N/E	
64742525	Naphthenic Petroleum Distillate	2-3						5 mg/m3	5 mg/m3	
64742467	Petroleum Distillate, Hydrotreated Middle	15.0 - 40.0						5 mg/m3 (m	5 mg/m3 (m	

### 3. HAZARDS IDENTIFICATION

**Hazard Category:**

Acute, Fire, Pressure

**Hazardous Identification Information:**

Flammable. Harmful or fatal if swallowed. Eye and Skin Irritant. Contents under Pressure.

Level 3 Aerosol

### 4. FIRST AID MEASURES

**Route(s) of Entry:**

Absorption, Eye, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

See Signs and Symptoms below

**Signs and Symptoms:**

**Eye Contact:**

Irritant. Prolonged contact may cause conjunctivitis.

**Skin Contact:**

Irritant. Defatting of tissue, dermatitis may occur.

**Inhalation:**

Irritant to mucous membranes. Repeated exposure may cause narcosis.

**Ingestion:**

HARMFUL OR FATAL IF SWALLOWED.:

**Medical Conditions Generally Aggravated by Exposure:** N/D

**Emergency and First Aid Procedures:**

**Eye Contact:**

Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

**Skin Contact:**

Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

**Inhalation:**

Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

**Ingestion:**

DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

**Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

**Product Name:** Silicone Lubricant  
**Item №:** MG-501

## 5. FIRE FIGHTING MEASURES

**Upper Explosive Limit:** N/D  
**Lower Explosive Limit:** N/D  
**Flash Point:** 125°F  
**Fire Extinguishing Media:** Water Fog, Foam, Carbon Dioxide, Dry Chemical  
**F.P. Method:** TCC

**Special Fire Fighting Procedures:** Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread. Use shield to protect from rupturing and venting containers.

**Unusual Fire and Explosion:** At elevated temperatures containers may vent, rupture or burst, even violently.

## 6. ACCIDENTAL RELEASE MEASURES

### Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

## 7. HANDLING AND STORAGE

**Precautions to be Taken:** Use with adequate ventilation and proper protective equipment. Store in cool, well ventilated area below 120°F away from heat sources. Do not use near fire, sparks, or open flame. Exposure to temperatures above 120° may cause container to vent, rupture, or burst. Do not puncture or incinerate container.

**Other Precautions:** Flammable. Store in cool place away from oxidizers and acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Ventilation Requirements:** See Section 2 for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

**Personal Protective Equipment:** See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** 310°F  
**Melting Point:** N/A  
**Evaporation Rate (Butyl Acetate = 1):** N/D  
**Vapor Pressure (mm Hg.):** N/D  
**Specific Gravity (H<sub>2</sub>O = 1):** 0.80200  
**Vapor Density (AIR = 1):** N/D  
**Solubility In Water:** Insoluble  
**Appearance and Odor:** Clear to slight yellow liquid with petroleum odor.  
**Other Information:** N/D

## 10. STABILITY AND REACTIVITY

**Stability:** Stable

**Incompatibility (Materials to Avoid):** Oxidizing agents and acids.

**Decomposition/By Products:** Normal products of combustion, carbon dioxide, smoke and Nitrogen and Sulfur Oxides

**Hazardous Polymerization:** Will not occur

**Product Name:** Silicone Lubricant  
**Item Nº:** MG-501

## 11. TOXICOLOGICAL INFORMATION

N/D

## 12. ECOLOGICAL INFORMATION

N/D.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL:** This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

## 14. TRANSPORT INFORMATION

**DOT (49CFR 172)**

### **Domestic Ground Transport**

**DOT Shipping Name:** CONSUMER COMMODITY

**Hazard Class:** ORM-D

**UN/ID Number:** None

**Marine Pollutant:** None

### **IMDG**

UN1950, AEROSOLS, CLASS 2.1, LTD QTY

EMS: F-D, S-U

BOXES OF 12 EACH 13.5 OZ METAL CAN, PLASTIC CAP

## 15. REGULATORY INFORMATION

See Section 2 for SARA Reportable Chemicals.

**USA TSCA:** All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

## 16. OTHER INFORMATION

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.  
KEEP AWAY FROM CHILDREN AND ANIMALS!

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 2, REACTIVITY 0

**Estimated HMIS Classification:** FLAMMABILITY 2, REACTIVITY 0, HEALTH 2

**N/E:** Not Established  
**N/D:** Not Determined  
**N/A:** Not Applicable  
**N/AV:** Not Available

Revision Date: 09/16/2013