

### PRODUCT DESCRIPTION

IMG® Radiator Super Flush protects the engine by restoring the efficiency of the coolant system, thereby allowing the engine to operate within the proper temperature range.

#### Application:

- For use as a short-time flush at the time of coolant change.
- Allows for one step cleaning.
- Use IMG® Radiator Super Flush whenever replacing coolant to maintain maximum engine protection from extreme heat generated by the engine.

### FEATURES

- Removes lime deposit, scale and solder bloom.
- Works to prevent engine overheating, ceasing, and excessive wear to engine components.
- Restores coolant circulation throughout the cooling system.
- Safe for all rubber, plastic, and metal components used throughout the cooling system.
- Safe and effective for all radiators and all types of coolants and antifreezes.

### DIRECTIONS FOR USE

Do NOT apply IMG® Radiator Super Flush to a hot radiator, engine, or cooling system.

1. Turn off the engine and allow it to cool.
2. Carefully open the cooling system drains and empty the contents of the cooling system into a proper container.
3. Close the drains.
4. Remove the radiator cap.
5. Pour one, 12 fl. oz. bottle of IMG® Radiator Super Flush directly into the radiator.
6. Fill the cooling system with water to the appropriate level, as recommended by the engine manufacturer.
7. Replace the radiator cap.
8. Start the engine and allow it to operate for about 10 minutes at idle.
9. Stop the engine, allow it to cool, and drain the coolant system once again, in accordance with steps 2-3.
10. Remove the radiator cap.
11. Fill the cooling system with the appropriate antifreeze or coolant, to the correct level, as recommended by the engine manufacturer.
12. Replace the radiator cap and check the system for leaks before starting the engine.

Dispose of ALL waste fluids in accordance with the proper safety procedures and the applicable environmental laws and regulations.

### COLOR

Bright Green

### SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830010440	Plastic Bottle	12 fl.oz
Net Weight	Per Case	Case Weight
0.8 lbs	12	11.6 lbs
Case Length	Case Width	Case Height
9.5"	10"	7.5"
Cases/Pallet*	Pallet Height*	Pallet Weight*

### STORAGE AND SHELF LIFE

Store in cool, dry, and well-ventilated area, in unopened containers. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. IMG® Radiator Super Flush has a general shelf life of 5 years from the date of manufacture.

### NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

