

PRODUCT DESCRIPTION

IMG[®] Radiator Sealer quickly eliminates minor cooling system leaks without clogging or damaging other cooling system components found in passenger vehicles and trucks.

FEATURES

- Stops leaks in radiators, engine blocks and heads, and in hoses and other components of cooling systems found in passenger vehicles and trucks.
- Restores effectiveness of seals in engine water pumps, thermostats, and heater control valves.
- Prevents the formation of hard calcium deposits inside radiators and engine blocks.
- Contains corrosion inhibitors to prevent rust and corrosion within cooling system components.
- Safe for all cooling system components.

DIRECTIONS FOR USE

Apply IMG[®] Radiator Sealer ONLY to a <u>warm</u> engine (But NOT to a <u>hot</u> radiator, engine, or cooling system).

- 1. Turn off engine and allow it to cool.
- 2. Remove the radiator cap.
- 3. Make sure that there is sufficient water or coolant in the radiator to at least cover the radiator core.
- 4. Turn on the engine and allow it to operate at idle for about 10 minutes with the heater set to its hottest setting.
- 5. Shake the bottle of IMG® Radiator Sealer well.
- 6. Pour the entire, 12 fl. oz. bottle of IMG[®] Radiator Sealer directly into the radiator.
- 7. If needed, fill the cooling system with water or the appropriate antifreeze or coolant, to the correct level, as recommended by the engine manufacturer.
- 8. Carefully replace the radiator cap.
- 9. Allow the engine to continue operating at idle for about 10 minutes to circulate the IMG[®] Radiator Sealer through the system and seal the leak.
- 10. If the leak does not stop, or if it re-starts, then a repair or replacement of mechanical components may be required.

COLOR Light brown

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830010457	Plastic Bottle	12 fl.oz
Net Weight	Per Case	Case Weight
0.7 lbs	12	11 lbs
Case Length	Case Width	Case Height
9.5"	10"	7.5"
Cases/Pallet*	Pallet Height*	Pallet Weight*

STORAGE AND SHELF LIFE

Storeincool, dry, and well-ventilated area, in unopened containers. Donot expose to heat, open flames, strong oxidizers or other sources of ignition. IMG® Radiator Sealer has a general shelf life of 5 years from the date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

