

PRODUCT DESCRIPTION

IMG® Diesel Water Remover is specially formulated to eliminate water droplets and condensation from diesel fuel in the fuel tank and fuel system, and to prevent water fallout and fuel filter icing at colder temperatures.

Commercially available diesel fuel has a typical water content of approximately 50 to 65 ppm (parts per million). This normal level of water poses almost no risk of damage to the engine, fuel pump, injectors, and other components. However, increased water content in the diesel fuel can cause corrosion and problems with performance and efficiency. Regular use of IMG® Diesel Water Remover will prevent such problems and possible damage.

Application:

- Removes water from diesel fuel and prevents icing over of fuel filters.
- Regular use (once a month during the winter) will insure condensation doesn't build up in the system.
- Helps keep fuel injectors free of water deposits that interfere with the fuel injector spray pattern and cause the engine to smoke, emit more emissions and reduce fuel economy.
- Recommended for use in all diesel engines found in passenger vehicles, trucks, heavy machinery, and specialized equipment.
- Prevents corrosion, rust and the reduction of lubricity of the fuel from water which can damage the fuel pump and pit, scar and destroy injector tips.

DIRECTIONS FOR USE

1. Turn off the engine.
2. Remove the vehicle's fuel filler cap.
3. Open the IMG® Diesel Water Remover by removing the cap from the bottle.
4. Carefully puncture or remove the seal underneath the cap.
5. Pour IMG® Diesel Water Remover directly into the fuel tank before re-fueling.
6. Replace the fuel filler cap and close it properly.

One bottle of IMG® Diesel Water Remover (12 fl. oz.) treats up to 21 gallons of fuel.

COLOR

Red dyed liquid

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830012017	Plastic Bottle	11.8 fl.oz
Net Weight	Per Case	Case Weight
0.6 lbs	12	9.2 lbs
Case Length	Case Width	Case Height
9.5"	10"	7.5"
Cases/Pallet*	Pallet Height*	Pallet Weight*

STORAGE AND SHELF LIFE

Store in a cool, dry, and well-ventilated area, away from sparks and flames. Empty containers may retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

IMG® Diesel Water Remover has a general shelf life of 5 years from the date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

