

PRODUCT DESCRIPTION

IMG® 5 Minute Motor Flush safely cleans internal engine components and removes sludge, rust, gum and varnish from the engine during an oil change.

FEATURES

- Dissolves deposits from pistons and rings and frees sticky valves and lifters.
- Improves performance, fuel economy and engine life.
- Helps to restore compression.
- pH Neutral formulation.
- Safe for engine components and all metal parts.
- Recommended for use in gasoline and diesel engines.
- Compatible with all commonly used types of oil.
- Helps to prevent future corrosion and prevent excessive wear to engine components.

DIRECTIONS FOR USE

1. Turn off the engine and allow it to cool.
2. Remove the engine oil filler cap.
3. Carefully pour one, 15 fl. oz. can of IMG® 5 Minute Motor Flush directly into the cool engine.
4. Check the oil level to make sure that there is enough oil to safely operate the engine.
5. Replace the engine oil filler cap.
6. Start the engine and allow it to operate for about 10 minutes at idle, to allow the IMG® 5 Minute Motor Flush to circulate through the engine.
7. Stop the engine and allow it to cool.
8. Open the engine oil drain valve and empty the waste oil from the engine into a proper container.
9. Close the drain valve.
10. Replace the used oil filter with a new filter.
11. Open the engine oil filler cap and re-fill the engine with the appropriate engine oil, to the correct level, as recommended by the engine manufacturer.
12. After making certain that the engine oil level is appropriate, replace the engine oil filler cap.

Dispose of ALL waste fluids in accordance with the proper safety procedures and the applicable environmental laws and regulations.

COLOR

Clear red liquid

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830010495	Metal Can	15 fl.oz
Net Weight	Per Case	Case Weight
15 oz	12	23.6 lbs
Case Length	Case Width	Case Height
7"	11.5"	16.5"
Cases/Pallet*	Pallet Height*	Pallet Weight*
60	48"	1416 lbs

STORAGE AND SHELF LIFE

Store in cool, dry, and well-ventilated area, in unopened containers. Do not expose to heat, open flames, strong oxidizers or other sources of ignition.

IMG® 5 Minute Motor Flush has a general shelf life of 5 years from the date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

