

PRODUCT DESCRIPTION

IMG® Diesel Fuel De-Gel is specially formulated to quickly re-liquefy gelled diesel fuel and de-ice frozen fuel filters in below freezing temperatures, in an emergency.

Application:

- Thaws diesel fuel in less than 30 minutes.
- Neutralizes and dissolves wax crystals within the fuel filter and fuel lines.
- Significantly lowers the pour point and filterability of diesel fuel.
- Removes water from diesel fuel and prevents icing over of fuel filters.
- Highly effective when added to diesel fuel before the onset of freezing temperatures.
- Recommended for use, in emergency situations, to restore functionality of diesel engines and fuel systems in passenger vehicles, trucks, heavy machinery, and specialized equipment.
- Absolutely safe for all components of diesel fuel systems; contains NO alcohol or chlorine.

DIRECTIONS FOR USE

1. Turn off the engine.
2. Disconnect the frozen fuel filter and remove from it any gelled fuel.
3. Open the IMG® Diesel Fuel De-Gel by removing the cap.
4. Carefully puncture or remove the seal underneath the cap.
5. Pour IMG® Diesel Fuel De-Gel directly into the fuel filter, filling it about half way.
6. Fill the remaining space in the fuel filter with diesel fuel and re-connect it to the fuel system.
7. Remove the vehicle's fuel filler cap.
8. Pour IMG® Diesel Fuel De-Gel directly into the fuel tank at a proportion of 1 part De-Gel to 200 parts diesel fuel.
9. Replace the fuel filler cap and close it properly.
10. Wait about 10 minutes.
11. Start the engine.

COLOR

Clear pinkish liquid

SHIPPING INFORMATION

| Barcode | Packaging | Net Volume |
|---------------|----------------|----------------|
| 817830012024 | Plastic Bottle | 1L |
| Net Weight | Per Case | Case Weight |
| 1.7 lbs | 12 | 23.8 lbs |
| Case Length | Case Width | Case Height |
| 13" | 13" | 9.5" |
| Cases/Pallet* | Pallet Height* | Pallet Weight* |
| 36 | 48" | 857 lbs |

STORAGE AND SHELF LIFE

Store in a cool, dry, and well-ventilated area, away from sparks and flames. Empty containers may retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. IMG® Diesel Fuel De-Gel has a general shelf life of 5 years from the date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

