

### PRODUCT DESCRIPTION

IMG® Fuel Resistant Gasket Maker is a gray solvent based semi-drying liquid gasket based on an elastomeric, synthetic rubber and designed for use in two cycle and four cycle engines.

IMG® Fuel Resistant Gasket Maker provides a long-lasting flexible seal with excellent adhesion to most surfaces. This sealant is intended for use on motorcycles, personal watercrafts, snowmobiles and all-terrain vehicles. It retains elastomeric properties at high temperatures from -65° to 400° F and perform well in a gasoline environment.

### FEATURES

- Solvent-based gasket maker for use in two cycle and four cycle engines
- Specially formulated for use on parts and in mechanisms that come into direct contact with gasoline and other, similar fluids
- Recommended for use as the primary gasket in engine crankcases, cam covers, cylinder head top covers, timing chain cases, center and end transmission covers, exhaust manifolds, and clutch housings

### DIRECTIONS FOR USE

1. Clean and dry surfaces. Surfaces should be free of dirt, grease, oil and old gasketing material.
2. Remove cap, puncture inner seal, screw on extension nozzle and cut nozzle to desired bead width.
3. Apply a continuous bead to both sealed surfaces, completely encircle all bolt holes.
4. Assemble parts after 1 minute. Do not over tighten bolts.
5. Remove nozzle and replace cap after use.

### COLOR

Light Grey

### GENERAL INFORMATION

IMG® Fuel Resistant Gasket Maker is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

### SHIPPING INFORMATION

| Barcode       | Packaging      | Net Volume     |
|---------------|----------------|----------------|
| 817830010815  | Carded Tube    |                |
| Net Weight    | Per Case       | Case Weight    |
| 3 oz          | 12             | 3.4 lbs        |
| Case Length   | Case Width     | Case Height    |
| 8.5"          | 8.5"           | 4.5"           |
| Cases/Pallet* | Pallet Height* | Pallet Weight* |
| 225           | 48"            | 765 lbs        |

### STORAGE AND SHELF LIFE

When stored in original, unopened containers at or below 90° F (32° C) IMG® Fuel Resistant Gasket Maker has a minimum shelf life of 36 months from the date of manufacture.

### NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

**IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.**

