

PRODUCT DESCRIPTION

IMG® Clear Adhesive Sealant is a non-slump, paste-like, one-component RTV multi-purpose silicone sealant designed for a wide variety of industrial sealing and adhesive applications. It cures at room temperature by reaction with moisture in the air to produce a durable, flexible silicone rubber. This sealant can be used in a number of diverse sealing and bonding applications such as space-filling rubber adhesive or formed-in-place gaskets. It has a broad serviceable temperature range. Cured material stays flexible for continuous use from -76°F and up to 450°F for intermittent use.

FEATURES

- Clear, silicone-based product firmly bonds and seals a wide variety of materials, including metal, glass, wood, plastic, ceramic, rubber, vinyl, and others.
- Product is designed to be viscous, and can be easily used on vertical surfaces without running.
- Recommended for bonding rubber seals, weather stripping components, and sound-proofing insulation.

DIRECTIONS FOR USE

1. Clean and dry surfaces. Surfaces should be free of dirt, grease, oil and old gasketing material.
2. Remove cap, puncture inner seal, screw on extension nozzle and cut nozzle to desired bead width.
3. Apply a continuous bead to one sealed surface, completely encircle all bolt holes.
4. Assemble parts immediately. Do not over tighten bolts.
5. Remove nozzle and replace cap after use.

COLOR

Clear

GENERAL INFORMATION

IMG® Clear Adhesive Sealant is not recommended for use in the following applications:

- Structural silicone glazing
- Joints where physical abuse or abrasion is likely to be encountered
- Prolonged water immersion
- Porous surfaces, such as masonry
- Building materials that might bleed oils, plasticizers or solvents – materials such as impregnated wood, oil-based caulks, green or partially vulcanized rubber gaskets or tapes

- Totally confined spaces, because the sealant requires atmospheric moisture for cure
- Surfaces sensitive to corrosion by acetic acid vapors (a byproduct of sealant cure)
- Surfaces that will be painted (paint will not stretch with the extensions of the sealant and may crack and peel); complete all painting prior to using sealant
- Bonding to secondary seal of insulating glass units sealed with two-part silicone sealants
- This product is neither tested nor represented as suitable for medical or pharmaceutical uses

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830010297	Carded Tube	
Net Weight	Per Case	Case Weight
3 oz	12	3.4 lbs
Case Length	Case Width	Case Height
8.5"	8.5"	4.5"
Cases/Pallet*	Pallet Height*	Pallet Weight*
225	48"	765 lbs

STORAGE AND SHELF LIFE

When stored in original, unopened containers at a temperature between (46° to 82°F) IMG® Clear Adhesive Sealant has a minimum shelf life of 36 months from the date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

