# **TECHNICAL DATA SHEET**





#### PRODUCT DESCRIPTION

IMG® Automotive Super Glue is a fast setting, low to medium viscosity adhesive designed to bond close fitting surfaces quickly. IMG® Automotive Super Glue offers viscosity and flow characteristics that are ideal for filling small gaps. IMG® Automotive Super Glue sets in seconds to form a permanent, transparent bond. Effective on metal, rubber, glass aluminum, ceramics, vinyl, alloys, plastics and other non-porous surfaces.

#### **Typical Applications**

- Automotive trim
  Logos
- Minor interior repairs
  Household repairs and more
- Knobs

#### **FEATURES**

- Ready to use
  Fills gaps to .004"
- No mixing
  Holding strength to 5000 psi
- · Permanent, transparent bond

#### **DIRECTIONS FOR USE**

- 1. Make sure the surfaces to be bonded are clean and dry.
- 2. Dispense a drop or drops to one surface only. Apply only enough to leave a thin film after compression.
- Press parts together and hold firmly for a few seconds. Good contact is essential. An adequate bond develops in less than one minute. (Maximum strength is achieved in 24 to 48 hours.)
- 4. Wipe off excess adhesive from the top of the container and recap. IMG® Automotive Super Glue, if left uncapped, may deteriorate by contamination from moisture in the air.
- Because IMG<sup>®</sup> Automotive Super Glue condenses by polymerization, sometimes whitening will occur on the surface of the container or the bonded materials. Should this happen, wipe surfaces well with acetone.

#### **COLOR**

Clear

#### **GENERAL INFORMATION**

## SETTING TIME (68°F, 65% R.H.)

Substrate	Set time/Full cure	
Steel	10 to 20 seconds	
Aluminum	7 to 15 seconds	
Neoprene	<5 seconds	
ABS	5 to 10 seconds	
Polycarbonate	10 to 20 seconds	
PVC	10 to 20 seconds	

#### SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830010341	Carded Tube	
Net Weight	Per Case	Case Weight
0.07 oz	12	205 lbs
Case Length	Case Width	Case Height
4"	6.5"	4.5"
Cases/Pallet*	Pallet Height*	Pallet Weight*
	п	lbs

#### STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), IMG® Automotive Super Glue has a shelf life of 12 months from date of shipment.

### NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

