

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 1 of 9

Version: 1.1

Revision Date: March 8, 2011

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Brand Name: Butyl Rubber Roof and Gutter Sealant CS521, CS522

Product Use: Sealant & Adhesive

Proper DOT Shipping: Caulking & Glaziers, NOI

DOT Hazard Classification: NONE

Molecular Formula: Mixture

NFPA Profile: Health 2 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

Company Contact Information

IMG Chemicals Corporation

P.O. Box 52461

Atlanta, GA 30355 USA

Emergency Telephone Number

CHEMTREC: 800-424-9300 (24 hours)

Telephone: H1(678) 513-69-23

2. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Acute Effects

Eye:	Direct contact may cause moderate irritation. Symptoms include stinging, tearing and redness.
Skin:	May cause moderate irritation. Symptoms may include redness and burning of skin.
Inhalation:	Irritates respiratory passages very slightly. Vapor overexposure may be harmful and cause drowsiness and irritation. May cause anesthetic effects and act as a central nervous system depressant.
Oral:	There are no known symptoms of ingestion.

Prolonged/Repeated Exposure Effects

Skin:	Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis. Overexposure by skin absorption may injure the following organ(s): Kidneys, Central Nervous System.
Inhalation:	Overexposure by inhalation may injure the following organ(s): Kidneys, Central Nervous System.
Oral:	Overexposure by ingestion may injure the following organ(s): Kidneys, Central Nervous System.

Other Health Effects

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 2 of 9

Version: 1.1

Revision Date: March 8, 2011

This product contains a chemical(s) that has the following effect(s):

Carcinogenicity

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

Eye or skin disease, breathing or respiratory disorders. Intentional misuse by deliberately concentrating and inhaling vapors can be harmful.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1317-65-3	<50%	Calcium Carbonate
30863-42-5	<50%	Copolymer of Isobutylene
8052-41-3	<30%	Mineral Spirits
148807-96-6	<10%	Talc
13463-67-7	<10%	Titanium Dioxide
1333-86-4	<10%	Carbon Black (CS521)

4. FIRST AID MEASURES

Eye:	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 – 20 minutes while holding the eyelid(s) open. Remove contact lens if present, DO NOT delay irrigation. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin:	Remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Flush with lukewarm gently flowing water for 15 minutes. If irritation persists, repeat flushing. If irritation persists, obtain medical advice.
Inhalation:	Remove subject to fresh air. If not breathing, clear airway and start mouth to mouth artificial respiration or use a bag mask respirator. Get Medical attention if ill effects persist. If victim is having trouble breathing, transport to medical care and, if available, give supplemental oxygen.
Oral:	Never give anything by mouth if victim is rapidly losing consciousness or convulsing. DO NOT INDUCE VOMITING. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Obtain medical attention.

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 3 of 9

Version: 1.1

Revision Date: March 8, 2011

Note to Physician: Chemical of exposure is mineral spirits which may be an irritant to eyes, skin, mucous membranes, respiratory and gastroesophageal tracts.

5. FIRE FIGHTING MEASURES

Flash Point: 105F/40C

General Hazard: This product and its vapors are combustible. Explosive in a contained area. Vapors are heavier than air and may travel along the ground or may be moved by ventilation. Vapors may be ignited by open flames, sparks, heaters, smoking, electric motors or other sources of ignition distant from use.

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Extinguishing Media: On large fires use fog, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or foam. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire Hazards: None.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Ventilate area. Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills.

7. HANDLING AND STORAGE

Use with adequate ventilation to keep area below established exposure levels. Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Avoid contact with clothing. Wash thoroughly after handling. Keep container closed. Do not take internally.

Use reasonable care and keep container closed. Store in a combustible material area. Do not store with strong acids, alkalis or oxidizers.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 4 of 9

Version: 1.1

Revision Date: March 8, 2011

Component Exposure Limits

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
1317-65-3	Calcium Carbonate	OSHA PEL 15 mg/m ³ , ACGIH TLV 10 mg/m ³
13463-67-7	Titanium Dioxide	OSHA PEL 15 mg/m ³ , ACGIH TLV 10 mg/m ³
148807-96-6	Talc	OSHA PEL 5 mg/m ³ , ACGIH TLV 2 mg/m ³
1333-86-4	Carbon Black	OSHA PEL 3.5 mg/m ³ , ACGIH TLV 3.5 mg/m ³
8052-41-3	Mineral Spirits	OSHA PEL 100 ppm, ACGIH TLV 100 ppm

Exposure limits are provided for information only. These chemicals are not in a respirable form in this product.

Engineering Controls

Local Ventilation: Recommended.

General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection – vented safety goggles as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator: Respiratory protection is normally not needed under ambient conditions. If vapor is generated when material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Personal Protective Equipment for Spills

Eyes: Use full face respirator.

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 5 of 9

Version: 1.1

Revision Date: March 8, 2011

Skin:	Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.
Inhalation/Suitable Respirator:	Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Precautionary Measures:	Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL & CHEMICAL PROPERTIES

Physical Form:	Paste
Color:	N/A
Odor:	Petroleum
Specific Gravity @ 25°C:	~1.28
Viscosity:	Not determined.
Freezing/Melting Point:	Not determined.
Boiling Point:	Not determined.
Vapor Pressure @ 25°C:	Heavier than air.
Vapor Density:	Heavier than air.
Solubility in Water:	Negligible
pH:	Not determined.
Volatile Content:	202 g/l (EPA Method #24)
Flash Point:	105F/40C
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.

Note: The above information is not intended for use in preparing product specifications.

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Conditions to Avoid:	Avoid temperatures above 120 °F.
Materials to Avoid:	Strong acidic, alkali and oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Metal oxides. Nitrogen oxides.

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 6 of 9

Version: 1.1

Revision Date: March 8, 2011

11. TOXICOLOGICAL INFORMATION

Component Toxicology Information

For Carbon Black

IARC- GROUP 2B (possibly carcinogenic to humans)

For Product

None

For Titanium Dioxide

Trochimowicz, et al.c J. Appl. Tox., 8, 383-385 (1988)

Oral LD (rat) >25g/kg

Dermal LD (rabbit) >10 g/kg

Inhalation LC (rat) >6.82 mg/l (4 hr)

Special Hazard Information on Components

None

12. ECOLOGICAL CONSIDERATIONS

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <=2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 7 of 9

Version: 1.1

Revision Date: March 8, 2011

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

14. TRANSPORT INFORMATION

DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

This material is considered hazardous.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings

Section 302 Extremely Hazardous Substances (40 CFR 355):

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

Acute:	No
Chronic:	No
Fire:	3
Pressure:	No
Reactive:	No

Section 313 Toxic Chemicals (40 CFR 372):

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 8 of 9

Version: 1.1

Revision Date: March 8, 2011

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Work Place Hazardous Material Information Sysytems (CRP Section 33)

This product has been classified according to the hazard criteria of the Controlled Products Regulation and the MSDS contains all required information.

3 Controlled Product: Classification: B3, D2B

Supplemental State Compliance Information

California

Warning: This product contains the following chemical chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

Crystalline Silica.

Florida

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
8052-41-3	<30%	Mineral Spirits

Massachusetts

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
8052-41-3	<30%	Mineral Spirits
1333-86-4	<10%	Carbon Black
13463-67-7	<10%	Titanium Dioxide

Minnesota

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
8052-41-3	<30%	Mineral Spirits
1333-86-4	<10%	Carbon Black
13463-67-7	<10%	Titanium Dioxide

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
-------------------	-------------	-----------------------

IMG Chemical Corporation

Material Safety Data Sheet

Butyl Rubber Roof and Gutter Sealant CS521, CS522

Page 9 of 9

Version: 1.1

Revision Date: March 8, 2011

8052-41-3	<30%	Mineral Spirits (SN1736)
1333-86-4	<10%	Carbon Black (SN 0342)
13463-67-7	<10%	Titanium Dioxide (SN 1861)

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
8052-41-3	<30%	Mineral Spirits
1333-86-4	<10%	Carbon Black
13463-67-7	<10%	Titanium Dioxide

Rhode Island

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
8052-41-3	<30%	Mineral Spirits
1333-86-4	<10%	Carbon Black
13463-67-7	<10%	Titanium Dioxide

16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.