

PRODUCT DESCRIPTION

IMG® Multi-Purpose Construction Adhesive is a proven high-quality, waterproof adhesive that creates a strong durable bond that remains flexible, bridges gaps up to 3/8" and offers up to 10 minutes working time.

RECOMMENDED FOR bonding common building materials. These products bond all common building materials, including:

- Plywood
- Paneling
- Molding
- Furring strips
- Ceramic fixtures
- Corkboard
- Hardboard
- Drywall

FEATURES

- Strong durable bond
- Bonds most common building materials
- Bond remains flexible
- Interior
- Adhesive can bridge gaps up to 3/8"
- 100% Satisfaction Guaranteed
- Exceeds ASTM C-557

DIRECTIONS FOR USE

Surface Preparations:

Make sure that all surfaces are clean, dry and structurally sound before product is applied. Cut and pre-fit materials prior to installation.

Applying The Product:

Insert IMG® Multi-Purpose Construction Adhesive cartridge into standard caulking gun. Cut nozzle at 45° angle to desired bead size marked on nozzle. Puncture inner seal with nail or wire.

Bonding Paneling to Furring Strips or Studs: Apply a zigzag 1/4" (.64 cm) bead of adhesive to each strip or stud to be covered by material. Position paneling so edges meet at stud center. Only severely warped materials will require finishing nails at top and bottom.

Bonding Panels, Corkboard, etc. to Flat Surfaces: Apply 1/4" (.64 cm) zigzag vertical adhesive bead a maximum of 12" (30 cm) apart, within 1-1/2" (3 cm) of all edges.

Quick-Bond Method: Press materials firmly into place and pull away for 3 to 5 minutes, then press back into place.

Clean-Up:

Use mineral spirits or an adhesive remover.

Disposal:

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants.

COLOR

Tan

GENERAL INFORMATION

NOT RECOMMENDED FOR finished flooring, subfloors, underlayment, mirrors, ceiling tiles, marble, granite or synthetic marble and granite.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011706	Cartridge	14 fl oz
Net Weight	Per Case	Case Weight
12.5 oz	12	11.4 lbs
Case Length	Case Width	Case Height
6.5"	8.5"	12"
Cases/Pallet*	Pallet Height*	Pallet Weight*
245	7 ft	2,793 lbs

* U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

IMG® Multi-Purpose Construction Adhesive is to be stored under controlled dry environment (below 75° F.) Use within 18 months from date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

