

PRODUCT DESCRIPTION

IMG® Kitchen & Bath Construction Adhesive provides an exceptional waterproof bond under extreme conditions and won't harm most tub surrounds and shower walls when directions are followed. Light color won't show through surrounds. Recommended for most plastic tub and shower enclosures.

RECOMMENDED FOR bonding most plastic tub and shower enclosures over structurally sound drywall, plywood, hardboard, ceramic tile, greenboard and cement backerboard. It is also recommended for polystyrene foamback tub kits when adhesive venting method described under "Applying The Product" is followed.

FEATURES

- No burn through
- Heat & steam resistant
- Great for polystyrene, plastic & fiberglass tub & shower units
- No bracing required
- Light cream color won't show through
- Strong, waterproof bond
- Interior
- 100% Satisfaction Guaranteed

DIRECTIONS FOR USE

Surface Preparations:

Make sure that all surfaces are clean, dry, structurally sound and free of any loose paint or other materials. Sand and roughen high gloss paint.

Applying The Product:

Do not apply Kitchen & Bath Construction Adhesive when surface or adhesive temperature exceeds 90°F. Cut nozzle at 45° angle to a 1/8" bead size. Puncture inner seal with nail or wire. Apply in a continuous 1/8" bead, following the tub surround manufacturer's instructions. Some tub surround manufacturers require adhesive bead to be spread out with a trowel. Consult tub surround installation instructions for specific recommendations.

It is important for proper installation that each panel be vented according to the following directions. Venting method: Apply Kitchen & Bath Construction Adhesive and press panel firmly to wall, then pull away. Wait 3-5 minutes, then press panel firmly back into place. For proper adhesion, after 20-30 minutes go around entire tub surround and press firmly over all flat surfaces. If any edges lift up, tape them to the wall with masking tape until adhesive dries. Let cure 24 hours.

Clean-Up:

Use mineral spirits or an adhesive remover.

Disposal:

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants.

COLOR

Tan

GENERAL INFORMATION

NOT RECOMMENDED FOR flooring applications, ceramics, mirrors, granite, marble (real or cultured), plastic, vinyl, ceiling tile, subfloors/underlayment, or 1/8" medium density fiberboard paneling.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011720	Cartridge	14 fl.oz
Net Weight	Per Case	Case Weight
13.4 oz	12	11 lbs
Case Length	Case Width	Case Height
6.5"	8.5"	12"
Cases/Pallet*	Pallet Height*	Pallet Weight*
245	7 ft	2,695 lbs

* U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

IMG® Kitchen & Bath Construction Adhesive is to be stored under controlled dry environment (below 75° F.) Use within 18 months from date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

