

PRODUCT DESCRIPTION

IMG® Paneling & Molding Construction Adhesive is a superior construction adhesive specially designed for projects like paneling and molding for a strong instant bond. The fast, sure hold provides precision placement and less nailing. Paneling & Molding Construction Adhesive offers a ten minute working time and an impact-resistant bond.

RECOMMENDED FOR installing:

- Paneling
- Wood molding
- Furring strips
- Plywood/hardboard
- Corkboard

FEATURES

- Strong instant bond
- 10 minute working time
- Retains precise placement
- Interior
- Reduces nailing
- 100% Satisfaction Guaranteed

DIRECTIONS FOR USE

Surface Preparations:

Make sure that all surfaces are clean, dry and structurally sound before product is applied.

Applying The Product:

Cut and prefit materials prior to installation. Insert tube into standard caulking gun. Cut nozzle at 45° angle to desired bead size marked on nozzle. Puncture inner seal with nail or wire.

Instant-Grab Method:

Paneling: Apply 1/4" bead of adhesive approximately 1" from edge of panel around the perimeter. Apply two zigzag 1/4" beads in the middle of the panel. Press panel firmly into place. Due to panel inconsistencies, for best results, bracing and/or nailing may be required.

Molding: Apply 1/4" zigzag bead to back of molding. Press molding firmly into place. Starting at one end, nail every 12".

Clean-Up:

Use mineral spirits or an adhesive remover.

Disposal:

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants.

COLOR

Tan

GENERAL INFORMATION

NOT RECOMMENDED FOR

- Uses other than paneling & molding installations
- Exterior use
- Use between non-porous surfaces
- 1/8" thick medium density fiberboard.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011737	Cartridge	14 fl.oz
Net Weight	Per Case	Case Weight
12.6 oz	12	11.5 lbs
Case Length	Case Width	Case Height
6.5"	8.5"	12"
Cases/Pallet*	Pallet Height*	Pallet Weight*
245	7 ft	2,818 lbs

* U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

IMG® Paneling & Molding Construction Adhesive is to be stored under controlled dry environment (below 75° F.) Use within 18 months from date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

