TECHNICAL DATA SHEET

CS411 Acrylic Siliconized Sealant



PRODUCT DESCRIPTION

IMG® Acrylic Siliconized Sealant is a premium grade multi-purpose siliconized acrylic latex sealant. Manufactured and developed to provide excellent adhesion to vinyl, aluminum, wood, sheet metal and most common building materials without the need of a primer. It has been specially developed for the use in the installation of windows & doors and has minimal shrinkage. IMG® Acrylic Siliconized Sealant cures rapidly to form a durable tight bond.

Applications

- · Window & Door Applications
- · Cultured Marble
- Tile
- Industrial Applications

FEATURES

- · Window & Door Approved
- · Excellent Flexibility
- · Clean Up with Water
- · Mildew Resistant
- · Paintable
- · 50 Year Durability
- Quick Curing

DIRECTIONS FOR USE

Surface Preparations:

The substrate must be clean, dry, frost free, and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

How To Use:

For Best Results, make sure surface is clean, dry and free of oil or grease. Cut tip of threaded end of cartridge. Thread nozzle on. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Sealant will gain a skin in 15 minutes and exhibit full cure within 24 hours. Can be applied in warm or cold conditions. Clean excess material with water. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

COLOR

White

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011744	Cartridge	10.1 fl.oz
Net Weight	Per Case	Case Weight
18.4 oz	12	10.8 lbs
Case Length	Case Width	Case Height
8''	6''	10''
Cases/Pallet*	Pallet Height*	Pallet Weight*
280	7 ft	3,024 lbs

^{*} U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

 IMG^{\circledR} Acrylic Siliconized Sealant is to be stored under controlled dry environment (below 75° F.) Use within 24 months from date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

