TECHNICAL DATA SHEET





PRODUCT DESCRIPTION

IMG® MultiPurpose 100% Silicone Sealant is a 100% mildew resistant, acetoxy-based high performance silicone designed for many applications. It is formulated as a one component, permanently flexible, silicone and offers excellent adhesion. It is recommended for high moisture areas such as marine, baths, and walk-in coolers.

Applications

- · Walk-In Cooler Applications
- · Kitchens & Bath Applications
- · Cultured Marble Applications
- · Marine Applications
- · Industrial Applications

FEATURES

- · 100% Anti-Microbial Formula
- · Food Grade Compliant
- · FDA/USDA Compliant
- · Approved for Cultured Marble
- · Excellent Adhesion
- · Non-Sag & Slump
- 75 Year Durability
- · Quick Curing
- · Consistent Gunablility & Tooling

DIRECTIONS FOR USE

Surface Preparations:

The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications

How To Use:

For Best Results, ensure surface is clean, dry and free of oil or grease. Cut tip of threaded end of cartridge. Thread nozzle on. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Sealant will gain a skin in 12 minutes and exhibit full cure within 24 hours. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

COLOR

Brown

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011812	Cartridge	10.1 fl.oz
Net Weight	Per Case	Case Weight
18.4 oz	12	9.7 lbs
Case Length	Case Width	Case Height
8'''	6.5''	9.5
Cases/Pallet*	Pallet Height*	Pallet Weight*
280	7 ft	2,716 lbs

^{*} U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

IMG[®] MultiPurpose 100% Silicone Sealant is to be stored under controlled dry environment (below 75°F.) Use within 18 months from date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

