

TECHNICAL DATA SHEET

CS521 Butyl Rubber Roof & Gutter Sealant

PRODUCT DESCRIPTION

IMG® Butyl Rubber Roof & Gutter Sealant is a one component, gun grade, permanently flexible, general purpose butyl rubber sealant manufactured for excellent adhesion to most common building materials and plastics without the need of a primer. IMG® Butyl Rubber Roof & Gutter Sealanthas excellent weatherability, non-staining, paintable and stays permanently elastic even when exposed to both high and low temperatures.

Applications

- · Window & Door Applications
- · Residential Building Applications
- · Industrial Applications

FEATURES

- · Window & Door Approved
- · Non-Sag & Slump
- · 50 Year Durability
- · Permanently Flexible
- Non-Staining
- Paintable
- · Excellent Adhesion to Many Materials

DIRECTIONS FOR USE

Surface Preparations:

The substrate must be clean, dry, frost free, and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

How To Use:

For Best Results, make sure surface is clean, dry and free of oil or grease. Cut tip of threaded end of cartridge. Thread nozzle on. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent. It is the user's responsibility to thoroughly test all proposed uses with any and/or all substrates.

COLOR

Black

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011928	Cartridge	10.1 fl. oz
Net Weight	Per Case	Case Weight
14.6 oz	12	12.7 lbs
Case Length	Case Width	Case Height
8"	6"	10"
Cases/Pallet*	Pallet Height*	Pallet Weight*
280	7 ft	3,556 lbs

^{*} U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

 IMG^{\circledR} Butyl Rubber Roof & Gutter Sealant is to be stored under controlled dry environment (below 75° F.) Use within 18 months from date of manufacture.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

