

PRODUCT DESCRIPTION

IMG® MS Polymer Multi-Purpose Adhesive Sealant is a high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. IMG® MS Polymer Multi-Purpose Adhesive Sealant cures rapidly when exposed to atmospheric moisture to form a durable bond and can be applied in a wide range of temperature and weather conditions (-35°F to 140°F).

Applications

- Perimeter sealing of windows, doors & skylights
- Siding
- Construction Flashing Applications
- Sealing Waterproof Membrane
- Industrial Applications

FEATURES

- AAMA Certified
- Non-Yellowing
- Environmentally friendly
- No Solvents, Very Low VOCs
- Can Be Painted in 2 hours
- Fast Cure at a wide range of temperatures
- Aggressive Adhesion to common construction substrates
- Compatible with SBS Flashing
- Wide application temperature range (-35°F to 140°F)

DIRECTIONS FOR USE

Surface Preparations:

For best results, prepare clean, dry surface. Cut tip of threaded end of cartridge. Thread nozzle on. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be painted within 2 hours depending upon bead size. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

How To Use:

The substrate must be clean, dry, frost free, and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

COLOR

White

SHIPPING INFORMATION

Barcode	Packaging	Net Volume
817830011935	Cartridge	10.1 fl.oz
Net Weight	Per Case	Case Weight
18.4 oz	12	15.4 lbs
Case Length	Case Width	Case Height
6"	8"	10"
Cases/Pallet*	Pallet Height*	Pallet Weight*
280	7 ft	4312 lbs

* U.S. Standard, Heat-Treated Wood Pallets 40" (101.6 cm) x 48" (121.9 cm)

STORAGE AND SHELF LIFE

IMG® MS Polymer Multi-Purpose Adhesive Sealant is to be stored in a controlled environment below 75°F. Product has a 10 month shelf life.

NOTE

The contents of this document, including all data and descriptions, are provided strictly for informational purposes. While the information contained herein is believed to be reliable, IMG Chemicals Corporation cannot assume responsibility for variations and/or nonconforming results obtained or observed by other parties whose product use, environment, and methods are outside of our control.

IMG CHEMICALS CORPORATION DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE THAT MAY ARISE FROM THE USE OF IMG PRODUCTS. IMG CHEMICALS CORPORATION SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS.

